

Granville FS-B 5W/30

1 Litre, 5 Litre & 20 Litre

PRODUCT DESCRIPTION

FS-B 5W/30 is a fully synthetic low emission engine oil specially formulated using the very latest additive technology to produce a low SAPS lubricant. It provides excellent wear protection and is safe for use in vehicles where a diesel particulate filter is fitted.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: SN/CF

ACEA: C3

BMW: LL-04

MB: 229.31, 229.51 & 229.52

VW: 505.00 & 505.01

GM: Dexos²

Opel: OV0401547-D30



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	0593	5020618005933
5 Litre	0594	5020618005940
20 Litre	0588	5020618005889

PRODUCT BENEFITS

- * Ensures lubricant performance over extended drain intervals
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

PRODUCT USAGE

For engines where this specification lubricant is required.

DIRECTIONS FOR USE

As recommended by the engine manufacturer.



Granville FS-B 5W/30

1 Litre, 5 Litre & 20 Litre

STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place out of the reach of children.

SHELF LIFE

5 years from date of manufacture.

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water
Percentage of Biodiesel	: Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.3	<12.5	12.3
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	7		7.98
Pour Point	ASTM D97	°C		-36	
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		10	
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			73.3
Density	ASTM D792	@ 15°C			0.85

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

